



**SAFETY VALVES WITH FREE DISCHARGE  
IN THE AIR**

MATERIALS

EN 12164 CW 614N BRASS

EN 1982 Cu Sn5 Zn5 Pb5 BRONZE

316 L STAINLESS STEEL

OVERPRESSURE 10%

BLOWDOWN 10%

TYPE	d0 Ø mm.	DN "G.	A mm.	B Ø mm.	H mm.	WEIGHT Kg.	K	LIFT mm.	PN	SET PRESSURE ADJUSTMENT RANGE bar
S10N	10	3/8 - 1/2	Hex. ch.22	-	84	0,185	0,84	4,5	40	0,4 ÷ 30
S10P	10		Hex. ch.22	44	101	0,235	0,84	4,5	40	0,4 ÷ 30
S10A	10		Hex. ch.22	-	90	0,200	0,84	4,5	40	0,4 ÷ 30
S15N	14,2	1/2 - 3/4	Hex. ch.28 / Ø 28	-	118	0,410	0,84	6,5	40	0,4 ÷ 30
S15P	14,2		Hex. ch.28 / Ø 28	53	136	0,475	0,84	6,5	40	0,4 ÷ 30
S15A	14,2		Hex. ch.28 / Ø 28	-	124	0,420	0,84	6,5	40	0,4 ÷ 30
H10N	10	1/2 - 3/4	Hex. ch.28 / Ø 28	-	118	0,430	0,96	6,5	100	2,0 ÷ 100
H10P	10		Hex. ch.28 / Ø 28	53	136	0,495	0,96	6,5	100	2,0 ÷ 100
H10A	10		Hex. ch.28 / Ø 28	-	124	0,440	0,96	6,5	100	2,0 ÷ 100