



SAFETY VALVES WITH FREE DISCHARGE IN THE AIR

MATERIALS

EN 12164 CW 614N BRASS

EN 1982 Cu Sn5 Zn5 Pb5 BRONZE

316 L STAINLESS STEEL

OVERPRESSURE 10%

BLOWDOWN 10%

TYPE	d0 Ø mm.	DN "G.	A mm.	B Ø mm.	H mm.	WEIGHT Kg..	K	LIFT mm.	PN	SET PRESSURE ADJUSTMENT RANGE bar
R20N	20	1	Ø35 / 36	-	96	0,420	0,83	9	6	0,4 ÷ 6,0
R20P	20		Ø35 / 36	60	113	0,480	0,83	9		0,4 ÷ 6,0
R20A	20		Ø35 / 36	-	108	0,490	0,83	9		0,4 ÷ 6,0
R30N	30	1 1/4 1 1/2	Ø50	-	110	0,840	0,77	13	6	0,4 ÷ 6,0
R30P	30		Ø50	75	136	0,990	0,77	13		0,4 ÷ 6,0
R30A	30		Ø50	-	142	1,100	0,77	13		0,4 ÷ 6,0
R40N	38	1 1/2 2	Ø60 Hex. ch60	-	125	1,190	0,71	16	6	0,4 ÷ 6,0
R40P	38		Ø60 Hex. ch60	87	152	1,360	0,71	16		0,4 ÷ 6,0
R40A	38		Ø60 Hex. ch60	-	157	1,450	0,71	16		0,4 ÷ 6,0