



**SAFETY VALVES WITH CONVEYED DISCHARGE**

**MATERIALS**

EN 12164 CW 614N BRASS

EN 1982 Cu Sn5 Zn5 Pb5 BRONZE

316 L STAINLESS STEEL

OVERPRESSURE 10%

BLOWDOWN 10%

**CONNECTIONS TYPE**

GAS MALE, GAS FEMALE, NPTM, NPTF, DIN, TRI CLAMP, SMS, OTHERS ON SPECIFIC REQUEST

TYPE	d0 Ø mm.	DN "G.	d1 Ø mm.	DN1 "G.	A mm.	B Ø mm.		C mm.		D Ø mm.		H mm.		WEIGHT Kg.		K	LIFT mm.	PN	SET PRESSURE ADJUSTMENT RANGE bar
						bronze	316 L	bronze	316 L	bronze	316 L	bronze	316 L	bronze	316 L				
S15C	14,2	3/4	20	1	32	42	47	37	47	41	54	142	147	0,950	1,020	0,82	6,5	IN 40 OUT 16	0,4 ÷ 30
S15CL												155	160	1,020	1,080				
S20C	19,2	1	26	1/1/2	40	51	54	46	54	53	60	192	195	2,050	1,950	0,82	8	IN 40 OUT 16	0,4 ÷ 30
S20CL												209	212	2,230	2,100				
H10C	10	1/2 3/4	20	1	32	42	47	37	47	41	54	124	147	1,000	1,070	0,95	6,5	IN 100 OUT 16	2,0 ÷ 100
H10CL												155	160	1,070	1,130				
H15C	14,2	1	26	1 1/2	40	51	54	46	54	53	60	192	195	2,150	2,050	0,95	8	IN 100 OUT 16	2,0 ÷ 100
H15CL												209	212	2,330	2,200				