



SAFETY VALVES FOR HIGH PRESSURE
MATERIALS
EN 12164 CW 614N BRASS
EN 1982 Cu Sn5 Zn5 Pb5 BRONZE
316 L STAINLESS STEEL
OVERPRESSURE 10%
BLOWDOWN 10%

TYPE	d0 Ø mm.	DN "G.	d1 Ø mm.	DN1 "G.	A mm.	B Ø mm.		C mm.		D Ø mm.		H mm.		WEIGHT Kg.		K	LIFT mm.	PN	SET PRESSURE ADJUSTMENT RANGE bar
						bronze	316 SS	bronze	316 SS	bronze	316 SS	bronze	316 SS	bronze	316 SS				
H2N	2.5	1/4 3/8	-	-	22	-	-	-	-	-	-	84	102	0,220	0,240	0,05	4,5	DA 100 A 400	10 ÷ 400
H2C		1/2	10	1/2		35	35	19	16	23	23	100	102	0,330	0,330				0,5 ÷ 100
H5N	5	1/4 3/8	-	-	22	-	-	-	-	-	-	84	102	0,220	0,240		6,5		10 ÷ 400
H5C		1/2	10	1/2		35	35	19	16	23	23	100	102	0,330	0,330				
HP4/5N	4/5	3/8 1/2	-	-	28	-	-	-	-	-	-	118	120	0,430	0,430	0,76	6,5	10 ÷ 400	
HP4C/5C		3/4	14	1/2		35	35	25	25	30	30	128	130	0,580	0,580				0,5 ÷ 100
HP10C	10	1/2 3/4	14	1/2	28	35	35	25	25	30	30	128	130	0,580	0,580	0,76	8	10 ÷ 400	
HHP7N	7	3/4 1	-	-	40	-	-	-	-	-	-	155	161	1,200	1,150	0,95			10 ÷ 400
HHP7C	7		26	3/4		51	54	46	54	53	60	192	195	2,350	2,300	0,96			
HHP10N	10	3/4 1	-	-	40	-	-	-	-	-	-	155	161	1,200	1,150	0,95			10 ÷ 200
HHP10C	10		26	3/4		51	54	46	54	53	60	192	195	2,350	2,300	0,96			