



INDUSTRIAL VALVES

BALL VALVES	
TYPE	FLOATING AND TRUNNION MONOBLOC - WAFER – SPLIT BODY - 2 PIECES 3 PIECES – SIDE AND TOP ENTRY
CONSTRUCTION	B 16.34 – API 6A - API 6D – BS 5351
SIZE	FROM 1/2" TO 60" REDUCED AND FULL BORE
CLASS	ANSI 150 - 300 - 600 – 800 - 900 – 1500 – 2500 – 4500 PSI 3000 – 6000 - 10000
END CONNECTIONS	THREADED – BW – SW FLANGED ACCORDING TO ANSI - API – DIN - BS
SPECIAL FEATURES	NACE MR 01.75 – FIRE SAFE METAL TO METAL SEAT – UNDERGROUND SERVICE GEAR – ELECTRIC AND PNEUMATIC ACTUATOR EXTENDED BONNET - CRYOGENIC SERVICE HEATING JACKET – PREVELDED NIPPLES
STANDARD MATERIALS	C.S. A105 – A 350 LF2 - A216 WCB S. S. A182 F304 – A182 F316 – A351 CF8 – A351 CF8M
SPECIAL MATERIALS	HASTELLOY – INCONEL – INCOLOY – MONEL TITANIUM – DUPLEX – SUPER DUPLEX BRASS - BRONZE