

PORTATA ARIA A 20°C IN Kg/h / AIR DISCHARGE CAPACITY Kg/h 20°C																								
TIPO VALVOLA VALVE TYPE	PRESSIONE DI TARATURA IN BAR / SET PRESSURE BAR																							
	0.4	1	1.5	2	2.5	3	3.5	4	4.5	5	6	7	8	9	10	12	14	16	18	20	22	25	28	30
R20	284	414	522	630	739	847	955	1064	1172	1280	1497	-	-	-	-	-	-	-	-	-	-	-	-	-
R30	599	874	1103	1332	1560	1789	2018	2247	2476	2105	3163	-	-	-	-	-	-	-	-	-	-	-	-	-
R40	887	1293	1631	1970	2309	2647	2986	3324	3663	4002	4679	-	-	-	-	-	-	-	-	-	-	-	-	-
S10	73	106	134	161	189	217	245	272	300	328	383	439	494	550	605	716	827	938	1049	1160	1271	1438	1604	1715
S15	146	214	270	325	381	437	493	549	605	661	773	885	997	1109	1220	1444	1668	1892	2116	2339	2563	2899	3234	3458
S20	268	390	493	595	697	800	902	1004	1106	1209	1413	1618	1822	2027	2231	2640	3049	3459	3868	4277	4686	5299	5913	6322
S25	425	620	783	945	1108	1270	1433	1595	1758	1920	2245	2570	2895	3220	3545	4195	4845	5494	6144	6794	7444	8419	9394	10044
S32	707	1031	1301	1571	1841	2111	2381	2651	2921	3192	3732	4272	4812	5352	5892	6972	8053	9133	10213	11293	12373	13994	15614	16694
S40	1049	1530	1930	2331	2731	3132	3533	3933	4334	4734	5536	6337	7138	7939	8740	10343	11945	13547	15150	16752	18355	20758	23162	24764
S15C-CL	143	209	263	318	372	427	482	536	591	645	755	864	973	1082	1191	1410	1628	1847	2065	2284	2502	2830	3157	3376
S20C-CL	261	381	481	581	681	781	880	980	1080	1180	1380	1579	1779	1979	2178	2578	2977	3376	3776	4175	4574	5173	5772	6172
S25C-CL	415	606	764	923	1081	1240	1399	1557	1716	1874	2192	2509	2826	3143	3460	4095	4729	5364	5998	6632	7267	8218	9170	9804
S32C-CL	690	1007	1270	1534	1797	2061	2325	2588	2852	3116	3643	4170	4697	5225	5752	6806	7861	8915	9970	11024	12079	13660	15242	16297
S40C-CL	1024	1493	1884	2275	2666	3057	3448	3839	4231	4622	5404	6186	6968	7750	8532	10096	11661	13225	14789	16353	17918	20264	22610	24175

PER AVERE LA PORTATA IN L/1' MOLTIPLICARE PER 13,837 / TO HAVE THE L/1' DISCHARGE CAPACITY, MULTIPLY FOR 13,837  
 PER AVERE LA PORTATA IN m³/h DIVIDERE PER 1,2045 / TO HAVE THE m³/h DISCHARGE CAPACITY, DIVIDE BY 1,2045  
 PER AVERE LA PORTATA IN Nm³/h' DIVIDERE PER 1,2479 / TO HAVE THE Nm³/h DISCHARGE CAPACITY, DIVIDE BY 1,2479

**PORTATA ARIA A 20°C IN Kg/h / AIR DISCHARGE CAPACITY Kg/h 20°C**

TIPO VALVOLA VALVE TYPE	PRESSIONE DI TARATURA IN BAR / SET PRESSURE BAR																							
	0.4	1	2	4	6	8	10	12	14	18	20	22	25	28	30	35	40	45	50	60	70	80	90	100
H2N-C	-	-	-	-	-	-	2.25	2.66	3.08	3.90	4.32	4.73	5.35	5.97	6.38	7.41	8.44	9.48	10.51	12.57	14.64	16.70	18.77	20.83
H5N-C	1.08	1.58	2.40	4.05	5.70	7.36	9.01	10.66	12.31	15.61	17.26	18.92	21.39	23.87	25.52	29.65	33.78	37.91	42.03	50.29	58.55	66.80	75.06	83.32
HP4N-C	-	-	-	-	-	-	5.76	6.82	7.88	9.99	11.05	12.11	13.69	15.28	16.33	18.98	21.62	24.26	26.90	32.19	37.47	42.75	48.04	53.32
HP5N-C	-	-	2.40	4.05	5.70	7.36	9.01	10.66	12.31	15.61	17.26	18.92	21.39	23.87	25.52	29.65	33.78	37.91	42.03	50.29	58.55	66.80	75.06	83.32
H10N	-	-	184	311	438	564	691	818	945	1199	1325	1452	1642	1833	1959	2277	2594	2911	3228	3962	4496	5130	5764	6398
H15N	-	--	371	627	883	1139	1394	1650	1906	2417	2673	2929	3312	3696	3952	4591	5230	5870	6509	7787	9066	10345	11623	12902
H10C	-	-	182	308	433	559	648	810	935	1186	1312	1437	1625	1814	1939	2253	2567	2880	3194	3822	4449	5077	5704	6332
HP10C	-	-	146	246	346	447	547	648	748	949	1049	1150	1300	1451	1551	1802	2053	2304	2555	3057	3559	4061	4563	5065
H15C	-	-	368	621	874	1127	1380	1633	1886	2392	2645	2898	3278	3657	3910	4543	5176	5808	6441	7706	8972	10237	11502	12767

TIPO VALVOLA VALVE TYPE VALVES	PRESSIONE DI TARATURA IN BAR / SET PRESSURE BAR																							
	120	150	180	200	240	260	280	300	320	350	380	400												
H2N-C	24.96	31.15	37.34	41.47	49.73	53.86	57.98	62.11	66.24	72.43	78.63	82.75	-	-	-	-	-	-	-	-	-	-	-	-
H5N-C	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
HP4N-C	63.89	79.74	95.60	106	127	137	148	159	169	185	201	211	-	-	-	-	-	-	-	-	-	-	-	-
HP5N-C	99.83	124	149	165	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

PER AVERE LA PORTATA IN L/1' MOLTIPLICARE PER 13,837 / TO HAVE THE L/1' DISCHARGE CAPACITY, MULTIPLY FOR 13,837  
 PER AVERE LA PORTATA IN m³/h DIVIDERE PER 1,2045 / TO HAVE THE m³/h DISCHARGE CAPACITY, DIVIDE BY 1,2045  
 PER AVERE LA PORTATA IN Nm³/h' DIVIDERE PER 1,2479 / TO HAVE THE Nm³/h DISCHARGE CAPACITY, DIVIDE BY 1,2479