

PORTATA VAPORE IN Kg/h / STEAM DISCHARGE Kg/h																							
TIPO VALVOLA VALVE TYPE	PRESSIONE DI TARATURA IN BAR / SET PRESSURE BAR																						
	0,5	0,75	1	1,25	1,5	1,75	2	2,25	2,5	2,75	3	3,25	3,5	3,75	4	4,5	5	5,5	6	7	8	10	12
S15C-CL	91	112	133	149	166	183	199	216	232	249	266	282	299	315	331	365	398	430	464	529	592	725	854
S20C-CL	166	205	242	273	304	334	365	395	425	455	486	516	546	577	605	667	772	787	848	966	1083	1325	1561
S25C-CL	263	326	385	433	483	531	579	628	675	723	772	820	867	916	961	1059	1155	1250	1346	1535	1720	2104	2479
S32C-CL	438	541	640	720	802	882	963	1044	1122	1201	1283	1363	1441	1523	1598	1760	1919	2078	2238	2552	2860	3498	4120
S40C-CL	650	803	949	1068	1190	1309	1428	1548	1664	1782	1903	2022	2138	2259	2371	2611	2847	3083	3320	3785	4242	5198	6112
H10C-CL	-	-	-	-	-	-	115	124	133	143	153	162	171	181	190	209	228	247	266	304	340	416	490
H15C-CL	-	-	-	-	-	-	231	250	269	288	308	327	347	366	384	423	461	499	537	612	686	840	989